

► 15" LCD DISPLAY



► FEATURES

- Distinctive aluminum alloy housing for added strength
- NeoV Optical Glass™
- Swift 12ms response time
- High 400 brightness
- Crisp 500 contrast ratio
- DVI ready for high quality signal
- S-Video* and CVBS* inputs
- Auto-adjustment for optimal setting
- Kensington® security slot
- VESA standard wall mount
- Available colors: black, white



► SPECIFICATION

Panel	Panel Type	TFT LCD	
	Panel Size	15.0" (381mm)	
	Max. Resolution	XGA 1024 x 768	
	Pixel Pitch	0.297mm	
	Brightness	400cd/m ² (Typical)	
	Contrast Ratio	500:1 (Typical)	
	Surface Treatments	Hard Coating (3H), Anti-glare Treatment	
	Viewing Angle (H/V)	140°/130° (Typical)	
	Display Color	16.7M	
	Response Time	12ms (GTG)	
Input	Frequency (H/V)	H: 30kHz - 60kHz V: 50Hz - 75Hz	
	Max. Pixel Clock	80MHz	
	Life Time	50,000hrs (Minimum)	
Connector	Analog	15-Pin D-Sub	
	Digital	29-Pin DVI-D	
	S-Video*	4-Pin Mini Din S-Video	
	CVBS*	CVBS Jack	
NeoV Optical Glass	Power	3-Pin AC Plug	
	Thickness	3.0mm (0.18")	
	Reflection Rate	<1%	
	Transmission Rate	>96%	
Tilt	Hardness	>6H (MOH's Rating)	
	Tilt	0° ~ +20°	
	Mounting	VESA FPMPMI Yes (100mm)	
Regulation Approval	Safety & EMI	FCC, UL/CUL, TUV/GS, CE, BSMI, CB, ISO 13406-2	
	VESA	DDC 1/2B, DPMS	
Power	Power AC Consumption	100 - 240V, 50 - 60Hz <48W (On) <4W (Stand-by) <2W (Off)	
	Dimensions	Net (W x H x D)	380 x 359 x 155mm (15.0" x 14.1" x 6.1")
		Packing (W x H x D)	445 x 490 x 225mm (17.5" x 19.2" x 8.9")
Weight	Net Weight	4.8Kg (10.6lbs)	
	Gross Weight	7.0Kg (15.4lbs)	
Packing	1 Pallet	40 Cartons	
	20' Container	480 Sets	
	40' Container	1040 Sets	

*Video inputs are optional functions

All specifications are subject to change without prior notice

G.COMM srl
 Via Donizetti, 22
 20040 CORNATE D'ADDA
 Milano - ITALY -
 tel. +39 039 6060420
 Fax +39 039 6926991
 info@gcomm-online.com
 www.gcomm-online.com

► 17" LCD DISPLAY



► FEATURES

- Distinctive aluminum alloy housing for added strength
- NeoV Optical Glass™
- Swift 4ms response time
- High 500 contrast ratio
- DVI ready for high quality signal
- S-Video* and CVBS* inputs
- Auto-adjustment for optimal setting
- Kensington® security slot
- VESA standard wall mount
- Available colors: black, white



► SPECIFICATION

Panel	Panel Type	TFT LCD	
	Panel Size	17.0" (432mm)	
	Max. Resolution	SXGA 1280 x 1024	
	Pixel Pitch	0.264mm	
	Brightness	300cd/m ² (Typical)	
	Contrast Ratio	500:1 (Typical)	
	Surface Treatments	Hard Coating (3H), Anti-glare Treatment	
	Viewing Angle (H/V)	140°/130° (Typical)	
	Display Color	16.7M	
	Response Time	4ms (GTG)	
Input	Frequency (H/V)	H: 30kHz - 80kHz V: 50Hz - 75Hz	
	Max. Pixel Clock	135MHz	
Connector	Life Time	50,000hrs (Minimum)	
	Analog	15-Pin D-Sub	
	Digital	29-Pin DVI-D	
	S-Video*	4-Pin Mini Din S-Video	
NeoV Optical Glass	CVBS*	CVBS Jack	
	Power	3-Pin AC Plug	
	Thickness	3.0mm (0.18")	
	Reflection Rate	<1%	
Tilt	Transmission Rate	>96%	
	Hardness	>6H (MOH's Rating)	
	Tilt	0° ~ +15°	
Mounting	VESA FPMPMI	Yes (100mm)	
Regulation Approval	Safety & EMI	FCC, UL/CUL, TUB/GS, CE, BSMI, CB, ISO 13406-2, GOST	
	VESA	DDC 1/2B, DPMS	
Power	Power AC Consumption	100 - 240V, 50 - 60Hz <48W (On) <4W (Stand-by) <2W (Off)	
	Dimensions	Net (W x H x D)	408 x 398 x 175mm (16.1" x 15.7" x 6.9")
		Packing (W x H x D)	495 x 510 x 228mm (19.5" x 20.0" x 9.0")
Weight	Net Weight	6.8Kg (13.9lbs)	
	Gross Weight	9.5Kg (20.9lbs)	
Packing	1 Pallet	40 Cartons	
	20' Container	400 Sets	
	40' Container	880 Sets	

*Video inputs are optional functions

All specifications are subject to change without prior notice

G.COMM srl
 Via Donizetti, 22
 20040 CORNATE D'ADDA
 Milano - ITALY -
 tel. +39 039 6060420
 Fax +39 039 6926991
 info@gcomm-online.com
 www.gcomm-online.com